

**5/16" gesneden pool**

**100% micro polyester  
Solution Dyed**

RUG  
Twinback®

POOLHOOGTE  
± 21 mm

TOTALE HOOGTE  
± 24 mm

POOLGEWICHT  
± 1.760 g/m<sup>2</sup>

TOTAAL GEWICHT  
± 2.865 g/m<sup>2</sup>

AANTAL NOPPEN/M<sup>2</sup>  
± 20 625

LICHTECHTHEID  
≥ 5

WATERECHTHEID  
≥ 4-5

WARMTEDOORLAATWEERST.  
± 0.15 m<sup>2</sup> K/W

BRANDKLASSE  
Efl (EN 13501-1)

**5/16" velours coupé**

**100% micro polyester  
Solution Dyed**

DOSSIER  
Twinback®

HAUTEUR DU VELOURS  
± 21 mm

HAUTEUR TOTALE  
± 24 mm

POIDS DU VELOURS  
± 1.760 g/m<sup>2</sup>

POIDS TOTAL  
± 2.865 g/m<sup>2</sup>

NOMBRE DE POINTS/M<sup>2</sup>  
± 20 625

RÉSISTANCE À LA LUMIÈRE  
≥ 5

RÉSISTANCE À L'EAU  
≥ 4-5

RÉSISTANCE THERMIQUE  
± 0.15 m<sup>2</sup> K/W

CLASSEMENT FEU  
Efl (EN 13501-1)

**5/16" Schnittpol**

**100% micro polyester  
Solution Dyed**

RÜCKEN  
Twinback®

POLHÖHE  
± 21 mm

GESAMTHÖHE  
± 24 mm

POLGEWICHT  
± 1.760 g/m<sup>2</sup>

GESAMTGEWICHT  
± 2.865 g/m<sup>2</sup>

NOPPEN/M<sup>2</sup>  
± 20 625

LICHTECHTHEIT  
≥ 5

WASSERECHTHEIT  
≥ 4-5

WÄRMEDURCHLASSWIDERST.  
± 0.15 m<sup>2</sup> K/W

BRANDKLASSE  
Efl (EN 13501-1)

**5/16" cutpile**

**100% micro polyester  
Solution Dyed**

BACKING  
Twinback®

PILE HEIGHT  
± 21 mm

TOTAL HEIGHT  
± 24 mm

PILE WEIGHT  
± 1.760 g/m<sup>2</sup>

TOTAL WEIGHT  
± 2.865 g/m<sup>2</sup>

TUFT DENSITY/M<sup>2</sup>  
± 20 625

LIGHT FASTNESS  
≥ 5

WATER RESISTANCE  
≥ 4-5

THERMAL RESISTANCE  
± 0.15 m<sup>2</sup> K/W

FIRE CLASS  
Efl (EN 13501-1)

EN14041  
**CE**  
19  
Balta Industries - Wakkensteenweg 2  
BE - 8710 Sint-Baafs-Vijve  
**DOP: 1010#BNOAEL**  
Textile Floor Covering EN1307  
DL NA PCP HCHO DS  
www.baltamediabank.com



Onder voorbehoud van wijzingen van de technische specificaties - Sous réserve de modifications techniques - Unter Vorbehalt von technischen Änderungen - All rights reserved to alter technical specification

600	700	910	920	950
ca 4m	•	•	•	•



600



950



910



920



700