

Specification Sheet

ULSTER VELVET WILTON				
9.1 SHOTT, 0.250” PILE HEIGHT, 564 TEX YARN COUNT				
Construction		Woven Wilton		
Backing Materials	Weft	Jute		
	Warp	Jute and Cotton		
Backing Coating		SB Latex		
Pile Composition		80% Wool, 20% Nylon		
		Metric	Imperial	Tolerances
Pitch		31.50 per DM	8 per inch	+/- 5%
Rows		35.83 per DM	9.1 per inch	+/- 5%
Pile Height Above Backing		6.35 mm	0.250 inch	+/- 10%
Total Pile Height		9.35 mm	0.368 inch	+/- 10%
Effective Pile Weight		910 g/m²	26.85 oz/yd²	+/- 10%
Total Pile Weight		1212 g/m²	35.74 oz/yd²	+/- 10%
Total Carpet Weight		2241 g/m²	66.10 oz/yd²	+/- 15%
Tuft Density		112,840 per m²	94,349 per yd²	+/- 7.5%
Yarn Count	2 ply	R564/tex2	2/55’s Dewsbury	+/- 3%
Weights are quoted at standard moisture regain. Ulster Carpets manufacture under a quality system BS EN ISO 9001: 2015 approved by British Standards Institution, Certified No FM 877				
PERFORMANCE SPECIFICATION				
Colour Fastness	Light	ISO 105-B02	Pastel - Minimum 4 Other – Minimum 5	
	Shampooing	BS1006	Minimum 4	
	Water	BS EN ISO 105-E01	Minimum 4	
	Rubbing	BS EN ISO 105-X12 (BS 1006)	Minimum 3-4	
Appearance Retention (Scale of 1-5 5= very little or no change)		ISO 10361	Grade 3	
Tuft Retention		ISO 4919	Min 600/gm/f	
Wear Index		5	Extra Heavy Wear	
Flammability				
Reaction to Fire (EN13501) Euro Class		EN11925 EN ISO 9239	Cfl S1	
Marine Flammability		MED-B-9840	Wheelmark Approved IMO Approved	
USA Flammability		ASTM E648 E662	Class 1	
VOC Emissions				
GLP Approved		GLP3278	Approved	
French VOC		C Rating	Approved	
Belgian VOC		NR 411381-01	Approved	