

ulster™

Specification Sheet

EN 14041



HABITUS CROFT			
Construction		Tufted 1/4" Texture	
Backing Materials	PP	Ultra Light Bac®	
100% wool			
Pile Composition			
	Metric	Imperial	Tolerances
Pile Height	6.0 mm		+/- 10%
Total Height	8.0 mm		+/- 10%
Pile Weight	1500 g/m²		+/- 5%
Total Weight	1900 g/m²		+/- 15%
Tuft Density	32,000 per m²		+/- 7.5%
Product Width	400/500 cm		
Tog Rating	1.60		+/- 15%
Yarn Count	3ply Z and 4ply S		
Weights are quoted at standard moisture regain. Ulster Carpets manufacture under a quality system BS EN ISO 9001 Certified No FM 877			
PERFORMANCE SPECIFICATION			
Colour Fastness	Light	ISO 105-B02	Minimum 4
	Water	BS EN ISO 105-E01	Minimum 4
	Rubbing	BS EN ISO 105-X12 (BS 1006)	Minimum 3-4
Tuft Retention		ISO 4919	Min 600/gm/f
Wear Index		EN 1307	Class 23
Flammability			
Reaction to Fire (EN13501) Euro Class		EN 14041	Efl
VOC Emissions			
French VOC		DEVL1101903D	A+ Rating
Belgian Regulation		C-2014/24239	PASS
AgBB		AgBB	PASS
Indoor Air Comfort		5.3a	PASS
Indoor Air Comfort GOLD		5.3a	PASS
EN-7171		2004	E1
BREEAM International		GN22: BREEAM	Compliant
LEED v4 (Outside US)		LEED v4	Compliant