

ROMA

LEGACY COLLECTION

CONSTRUCTION STRUCTURE STRUKTUR STRUCTUUR	Tufting 5/64" cut pile Tufté 5/64" cut pile Getuftet 5/64" cut pile Getuft 5/64" cut pile	FASTNESS TO LIGHT SOLIDITÉ A LA LUMIÈRE LICHTECHTHEIT LICHTECHTHEID	EN ISO 105-B02 ≥ 5-6
PILE MATERIAL COMPOSITION DU VELOURS POLMATERIAL POOLMATERIAAL	100% PA	COLOUR FASTNESS TO WATER SOLIDITÉ À L'EAU WASSERECHTHEIT WATERECHTHEID	EN ISO 105-E01 ≥ 4-5
SECONDARY BACKING DOSSIER RÜCKEN TAPIJTRUG	Twin back	FIRE RESISTANCE COMPOTEMENT AU FEU BRENNVERHALTEN BRANDGEDRAG	EN 13501-1 C _{FL} -s1 if glued
PILE WEIGHT POIDS DU VELOURS POLEINSATZGEWICHT POOLGEWICHT	± 750 gr/m ²	WIDTH LARGEUR BREITE BREEDTE	EN ISO 3018 ca. 400, 500 cm
TOTAL WEIGHT POIDS TOTAL GESAMTGEWICHT TOTAAL GEWICHT	± 1.700 gr/m ²		
PILE THICKNESS EPAISSEUR DU VELOURS POLDICKE POOLDIKTE	± 6 mm		
TOTAL THICKNESS EPAISSEUR TOTALE GESAMTDICKE TOTAAL DIKTE	± 8,5 mm		
TUFT DENSITY NOMBRE DE POINTS NOPPENZAHL AANTAL PUNTEN	± 405.000/m ²		
PRODIS / GUT	9138F77C		
CLASSIFICATION CLASSEMENT KLASSIFIKATION CLASSIFICATIE	EN 1307 23/31 - LC3		



ITC CO BV
Kanegemstraat 15, B-8700 Tielt
itc-carpet.com

EN 14041

20
ITC CO BV
Kanegemstraat 15 - BE 8700 Tielt
DOP: 1011#IE00CV
Textile Floor Covering EN1307
Notified Body 2401
    
my.itc-carpet.com